






Matchcode	Description	Picture	Technical data	Colours
POL 102 Ni / ..(colour)	Terminal post <ul style="list-style-type: none"> with insulating rings with undetachable toogle head 		terminal: Nut 8 x 0.75 transition resistance: < 0.4 mΩ rated voltage: 1.000 V rated current: 100 A operating temperature: -25 °C...+115 °C max. torque for nuts: 6 Nm	black, red blue, yellow green, green-yellow
POL 201 Ni / ..(colour)	Terminal post <ul style="list-style-type: none"> with insulating rings with undetachable toogle head 		terminal: Nut 12 x 1 transition resistance: < 0.3 mΩ rated voltage: 1.000 V rated current: 200 A operating temperature: -25 °C...+115 °C max. torque for nuts: 15.5 Nm	black, red blue, yellow green, green-yellow
AK 4732 Cu	Crocodile clip <ul style="list-style-type: none"> not insulated socket terminal Ø 4 mm contact: crocodile jaws grips up to Ø 8 mm 		terminal: socket transition resistance: < 5 mΩ rated voltage: 33 VAC / 70 VDC rated current: 10 A operating temperature: -40 °C...+110 °C	-
TUE 4023 / GN	Insulator insulator for crocodile clip AK 4732 Cu		-	green
AK 7002 Ni / ..(colour)	Crocodile clip <ul style="list-style-type: none"> insulated socket terminal Ø 4 mm contact: crocodile jaws grips up to Ø 6 mm 		terminal: socket transition resistance: < 15 mΩ rated voltage: 33 VAC / 70 VDC rated current: 6 A operating temperature: -25 °C ...+60 °C	black, red blue, yellow green

PRC Technologies Corporation Ltd.

328/65 Ladprao 87 Rd., Wangthonglang, Bangkok 10310, Thailand.

Tel : +66(2) 530-7403-4, 092-864-7711

Fax : +66(2) 530-1731

328/65 ซอยลาดพร้าว 87 แขวงวังทองหลาง เขตวังทองหลาง กรุงเทพฯ 10310

E-mail : contact@prctech.net