

XS Cond 50 VioLab Bench conductivity meter - Cell 2301 T

Item Code: 50103002



DATA SHEET

Features

Accuracy (Cond)	±2 % f.s.
Accuracy (Temperature)	±0,5 °C
Power supply	100 - 240 V
Temperature coefficient (max)	0,00 ... 10,00 % / °C
Temperature compensation	0,0 ... 100,0 °C
Cell constant	0.1 / 1 / 10 selectable
Description	Complete with 2301T cell with built-in temperature sensor, 1 m fixed cable
Display	High-definition, backlit colour LCD
TDS factor	0,40 ... 1,00
Stability filter	3 levels
IP rating	54 IP
Online help	Yes
Buffer used indication	Yes with icon
Inputs	BNC - RCA
Name	Cond 50 VioLab
Weight	0.38 kg
Calibration points Cond	1 ... 4
Cond measuring range	0,00 µS ... 200 mS
TDS measuring range	0.1 mg/l ... 200 g/l
temperature measurement range	0,0 ... +100,0 °C
Calibration Report	Yes
Cond resolution	0,01 - 0,1 - 1 µS / 0,01 - 0,1 mS µS/cm - mS/cm
Temperature resolution	0,1 °C
Swabs recognised Cond	84 µS - 147 µS - 12,88 µS - 111,8 µS - 1 valore user
Working temperature	0 ... +45 °C
Reference temperature	+15 ... +30 °C

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824