

XS Cond 60 VioLab Bench conductivity meter - Cell 2301 T

Item Code: 50103072



DATA SHEET

Features

Accuracy (Cond)	±2 % f.s.
Accuracy (Temperature)	±0.5 °C
Power supply	100 - 240 V
Temperature coefficient (max)	0,00 ... 10,00 % / °C
Temperature compensation	0,0 ... +100,0 °C
PC Communication	Micro USB
Description	Complete with 2301T cell with built-in temperature sensor, 1 m fixed cable
Display	High-definition, backlit colour LCD
TDS factor	0.40 ... 1.00
Stability filter	3 levels
AQA	Yes
IP rating	54 IP
Online help	Yes
Buffer used indication	Yes with icon
Inputs	BNC - RCA
Memory	1000
Name	Cond 60 VioLab
Output	Micro USB - RS 232
Weight	0.38 kg
Calibration points Cond	1 ... 4
Cond measuring range	0.00 µS ... 200 mS
Salinity measuring range	0,1 ppm ... 100 ppt
TDS measuring range	0.1 mg/l ... 200 g/l
temperature measurement range	0.0 ... 100.0 °C
Calibration Report	Yes, printable
Cond resolution	0,01 µS/cm - mS/cm
Temperature resolution	0.1 °C

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824

Calibration due with alarm

Yes

Working temperature

0 ... +45 °C

Reference temperature

+15 ... +30 °C

DS_50103072_rev. _16-12-2024

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824