

XS PC 7 Vio portable multiparameter - Without electrode - Without Cell

Item Code: 50110742



DATA SHEET

Features

Accuracy (Cond)	±2 % f.s.
Accuracy (pH)	±0,02 pH
Accuracy (Temperature)	±0,5 °C
Power supply	3 x AA batteries 1.5 V
Temperature calibration	Yes
Temperature coefficient (max)	0,00 ... 10,00 % / °C
DHS compatibility	Yes
Temperature compensation	0,0...80,0 °C
Automatic brightness control	Yes
Cell constant	0,1 / 1 / 10
Criteria for stability of the measure	Low - Med - High (pH)
Without pH electrode and without conductivity cell, with NT55, S7-BNC cable and accessories	
Description	
Display	High-definition, backlit colour LCD
TDS factor	0.40 ... 1.00
IP rating	57 IP
Online help	Yes
Calibration data indication	Yes
Buffer used indication	Yes with icons
Inputs	BNC - RCA
Name	PC7 VioLab
Regulations	CE
Parameters	pH, mV, ORP, Conducibilità, TDS, Temperatura
Weight	0.4 kg
Calibration points Cond	1...4
ORP calibration points	1
PH calibration points	1...3 automatic values - 2 user values
Cond measuring range	0,00 µS ... 200 mS

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824

mV ORP measuring range	-1000 ... +1900 mV
pH measuring range	0 ... +14,00 pH
TDS measuring range	0.1 mg/l ... 200 g/l
temperature measurement range	0,0 ... +100,0 °C
Cond resolution	0,01 / 0,1 / 1 (scala automatica) µS/cm - mS/cm
ORP resolution	1 mV
pH resolution	0,01 pH
Temperature resolution	0,1 °C
Swabs recognised Cond	84 µS - 147 µS - 1413 µS - 12,88 mS - 111,8 mS - 1 valore user
Recognised pH buffers	USA - NIST
Working temperature	0 ... +45 °C
Reference temperature	+15 ... +30 °C
Cell type	2 rings

DS_50110742_rev. _14-12-2024

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824