

XS PC 70 Vio portable multiparameter - Without electrode - Without Cell

Item Code: 50110842



DATA SHEET

Features

Accuracy (pH)	±0,02 pH
Accuracy (Temperature)	±0,5 °C
Power supply	3 x AA batteries 1.5 V
Temperature calibration	Yes
Temperature coefficient (max)	0,00 ... 10,00 % / °C
DHS compatibility	Yes
Temperature compensation	0,0 ... 100,0 °C
PC Communication	Micro USB
Automatic brightness control	Yes
Cell constant	0,1 / 1 / 10
Criteria for stability of the measure	Low - Med - High (pH)

Without pH electrode and without conductivity cell, with
NT55, S7-BNC cable and accessories

Description	
TDS factor	0.40 ... 1.00
AQA	Yes
Inputs	BNC - RCA
Memory	1000 data
Name	PC 70 VioLab
Parameters	pH, mV, ORP, Conducibilità, TDS, Salinità, Temperatura
Weight	0.4 kg
PH calibration points	1...3 automatic values - 2 user values
mV ORP measuring range	-1000 ... +1900 mV
pH measuring range	-2,00 ... +16,00 pH
Salinity measuring range	0,1 ppm ... 100 ppt
Cond resolution	0,01 / 0,1 / 1 (scala automatica) µS/cm - mS/cm
ORP resolution	0,1 mV
pH resolution	0,01 pH
Temperature resolution	0,1 °C

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824

Timer calibration due with alarm

Si

Cell type

2 rings

DS_50110842_rev. _14-12-2024

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824